

# URL d'accès

<url\_site\_ezged>/apps/ezuploader/

Exemple: <http://localhost/ezged/apps/ezuploader/>

## Paramétrage

Le passage des paramètres de l'application s'effectue via la query string (paramètres dans l'URL). La ressource doit retourner du JSON (le nom de la propriété racine contenant la liste des items doit être "rows").

Exemple de retour JSON valide:

[chemins\\_depots.json](#)

```
{  
    "rows" : [  
        {"description": "Foo sur disque D:", "chemin": "D:\\\\test\\\\foo"},  
        {"description": "Bar sur disque D:", "chemin": "D:\\\\test\\\\bar"}  
    ]  
}
```

## Paramètres requis

1. **qryid / service / url** ⇒ le nom du paramètre et la valeur attendue dépend du type de source
2. La description de la destination ⇒ paramètre **desc\_field** qui indique le nom de la propriété de l'item à lire pour avoir la description.
3. La chemin de destination ⇒ paramètre **value\_field** qui indique le nom de la propriété de l'item à lire pour avoir le chemin

## Types de ressources

### Requête EzGED

Nom du paramètre source : **qryid**

Valeur du paramètre source: un identifiant de requête ezged.

Exemple:

[http://localhost/ezged/apps/ezuploader/?qryid=721&desc\\_field=DEPOTCOLD\\_DESC&value\\_field=DEPOTCOLD\\_DIR](http://localhost/ezged/apps/ezuploader/?qryid=721&desc_field=DEPOTCOLD_DESC&value_field=DEPOTCOLD_DIR)

Le contenu de la ressource au format json:

```
{
  "errorcode": 0,
  "errormsg": "ok",
  "rows": [
    {
      "DEPOTCOLD_ID": 4,
      "DEPOTCOLD_DESC": "Répertoire foo dans ocr/wait",
      "type": "row",
      "DEPOTCOLD_DIR": "foo"
    },
    {
      "DEPOTCOLD_ID": 3,
      "DEPOTCOLD_DESC": "Répertoire bar dans ocr/wait",
      "type": "row",
      "DEPOTCOLD_DIR": "bar"
    },
    {
      "DEPOTCOLD_ID": 2,
      "DEPOTCOLD_DESC": "Répertoire exemple1",
      "type": "row",
      "DEPOTCOLD_DIR": "D:\\exemple1"
    },
    {
      "DEPOTCOLD_ID": 1,
      "DEPOTCOLD_DESC": "Répertoire exemple2",
      "type": "row",
      "DEPOTCOLD_DIR": "D:\\GED\\exemple2\\"
    }
  ],
  "count": 4
}
```

## Service EzGED

Nom du paramètre source : **service**

Valeur du paramètre source: chaîne d'appel d'un service ezged.

Exemple:

[http://localhost/ezged/apps/ezuploader/?service=coldscnthrower/loadall&coldscnthrowerproto=4&desc\\_field=COLDSCNTHROWER\\_DESC&value\\_field=COLDSCNTHROWER\\_PATH](http://localhost/ezged/apps/ezuploader/?service=coldscnthrower/loadall&coldscnthrowerproto=4&desc_field=COLDSCNTHROWER_DESC&value_field=COLDSCNTHROWER_PATH)

On appelle ici le service *coldscnthrower/loadall&coldscnthrowerproto=4* qui permet d'obtenir la liste des lanceurs COLD de type “Répertoire local”.

Contenu de la ressource au format json:

```
{
  "errorcode": 0,
```

```

"errmsg": "ok",
"rows": [
    {
        "COLDSCNTHROWER_ID": 130,
        "COLDSCNTHROWER_PORT": 0,
        "COLDSCNTHROWER_PASSWORD": "",
        "COLDSCNTHROWER_PROTO": 4,
        "COLDSCNTHROWER_HOST": "",
        "COLDSCNTHROWER_USER": "",
        "COLDSCNTHROWER_PATTERN": "./.*\\.(?!txt).*/",
        "COLDSCNTHROWER_PATH": "C:\\\\nchp\\\\var\\\\spool\\\\ezged\\\\instance\\\\ocr\\\\wait\\\\one",
        "COLDSCNTHROWER_DESC": "Indexeur One",
        "COLDSCNTHROWER_OLDERTHANINSEC": 0,
        "type": "coldscnthrower"
    },
    {
        "COLDSCNTHROWER_ID": 136,
        "COLDSCNTHROWER_PORT": 0,
        "COLDSCNTHROWER_PASSWORD": "admin",
        "COLDSCNTHROWER_PROTO": 4,
        "COLDSCNTHROWER_HOST": "",
        "COLDSCNTHROWER_USER": "admin",
        "COLDSCNTHROWER_PATTERN": "*.*",
        "COLDSCNTHROWER_PATH": "F:\\\\nchp\\\\var\\\\spool\\\\ezged\\\\instance\\\\ocr\\\\wait\\\\test",
        "COLDSCNTHROWER_DESC": "Lanceur Test",
        "COLDSCNTHROWER_OLDERTHANINSEC": 0,
        "type": "coldscnthrower"
    }
],
"count": 0
}

```

## Autre ressource

Nom du paramètre source : **url**

Valeur du paramètre source: l'url à appeler.

/!\ Attention: la ressource doit être relative au site ezged.

Exemple:

[http://localhost/ezged33/apps/ezuploader/?url=resources/chemins\\_depots.json&desc\\_field=description&value\\_field=chemin](http://localhost/ezged33/apps/ezuploader/?url=resources/chemins_depots.json&desc_field=description&value_field=chemin)

Contenu de la ressource au format json:

[chemins\\_depots.json](#)

```
{

```

```

    "rows" : [
        {"description": "Foo sur disque D:", "chemin": "D:\\test\\foo"},
        {"description": "Bar sur disque D:", "chemin": "D:\\test\\bar"}
    ]
}

```

## Intégration dans l'interface utilisateur

En suivant les indications ci-dessus pour la construction de l'URL d'appel de l'application vous pouvez créer un lien dans l'interface EzGED vers l'application. Ainsi vous aurez une zone d'upload accessible depuis l'interface EzGED.

Captures d'écrans:

The screenshot shows the EzGED Administration interface with the 'Administration' tab selected. In the top navigation bar, 'Accueil', 'Travaux', 'Sécurités', and 'Corbeilles' are visible. On the left, there's a sidebar with icons for 'Tableau de bord', 'Liens', and 'Mise à jour'. The main content area displays a table titled 'Liste des liens webs' with the following data:

	Adresse url	Mode
Libellé	<a href="https://www.ezdev.fr/satellite.php">https://www.ezdev.fr/satellite.php</a>	Node
Satellite	<a href="http://localhost/ezged3satellite/testsession.php">http://localhost/ezged3satellite/testsession.php</a>	1
Test session	<a href="http://requests kennethreitz.org/en/master/user/quickstart/">http://requests kennethreitz.org/en/master/user/quickstart/</a>	Dans la fenêtre Accueil
Quickstart requests	<a href="http://localhost/ezged/apps/ezuploader/service=coldsonthrower/localhost&amp;desc_field=COLDSCNTHROWER_DESC&amp;value_field=COLDSCNTHROWER_PATH">http://localhost/ezged/apps/ezuploader/service=coldsonthrower/localhost&amp;desc_field=COLDSCNTHROWER_DESC&amp;value_field=COLDSCNTHROWER_PATH</a>	Dans la fenêtre Accueil
Envoyer vers un lanceur		

The screenshot shows the EzGED user interface with the 'Accueil' tab selected. The left sidebar includes icons for 'Tableau de bord', 'Recherche', 'Travaux', 'Corbeille', 'Profil', and 'Liens'. The main area has tabs for 'Archives', 'Bannette', 'Workflow', 'Porapheur', and 'Indexation' (which is active, showing a count of 496). On the left, a sidebar lists 'Mes items' with options like 'Envoyer vers un lanceur', 'Quickstart requests', 'Satellite', and 'Test session'. The central part shows an 'Espace de dépôt' with a search bar and a 'Destination:' dropdown menu. The dropdown menu is open, showing a list of indexers and other items, with 'Indexeur One' highlighted. To the right, there's a large icon of a document with an upward arrow.

From:

<https://wiki.ezdev.fr/> - EzGED Wiki

Permanent link:

<https://wiki.ezdev.fr/doku.php?id=ezuploader&rev=1588166240>

Last update: 2023/03/17 09:56